

SPECIFICATIONS

GENERAL				
Frequency coverage*1 (Unit: MHz)				
Receiver	0.030-60.000*2			
Transmit	0.1357-0.1378	1.810-1.999	3.500-3.800	7.000-7.200
	10.100-10.150	14.000-14.350	18.068-18.168	21.000-21.450
	24.890-24.990	28.000-29.700	50.000-52.000	
*1 Showing EUR version. Varies according to version. *2 Some frequency bands are not guaranteed.				
Mode	USB, LSB, CW, RTTY, PSK31/63, AM, FM			
No. of memory channels	101 (99 regular, 2 scan edges)			
Antenna connector	SO-239x4 and BNCx2 (50Ω unbalanced (Tuner off))			
Operating temp. range	0°C to +50°C; +32°F to +122°F			
Frequency stability	Less than ±0.05ppm (0°C to +50°C @ 54MHz, after warm up)			
Frequency resolution	1Hz (minimum)			
Power supply requirement	85-265V AC			
Current drain	TX: 800VA (Max. power)			
	RX: 130VA/120VA typ. (Max. audio/standby)			
Dimensions (WxHxD, projections not included)	425x149x435 mm; 16.73x5.87x17.13 in			
Weight (approximate)	23.5 kg; 51.8 lb			
TRANSMITTER				
Output power	SSB/CW/FM/RTTY/PSK: 5-200W			
	AM: 5-50W			
Modulation system	Transverter connector (CW): More than -20dBm			
	SSB : Digital P.S.N. modulation			
	AM : Digital low power modulation			
Spurious emissions	FM : Digital phase modulation			
	HF bands: More than 60dB			
Carrier suppression	50MHz band: More than 70dB			
	More than 63dB			
Unwanted sideband suppression	More than 70dB			
ΔTX variable range	±9.999kHz			
Microphone impedance	600Ω (8-pin connector)			

All stated specifications are subject to change without notice or obligation.

RECEIVER			
Receive system	Double conversion super-heterodyne system		
Intermediate frequencies	Main receiver: 64.455MHz/36kHz (1st/2nd)		
	Sub receiver: 64.555MHz/36kHz (1st/2nd)		
Sensitivity (typical)	(HF: Pre-amp 1 ON, 50MHz: Pre-amp 2 ON)		
	0.1-1.799MHz	1.8-29.990MHz	50-54MHz
	SSB, CW, RTTY, PSK (BW=2.4kHz, at 10dB S/N)	0.5μV	0.16μV
AM (BW=6kHz, at 10dB S/N)	6.3μV		2μV
	2μV		1μV
FM (BW=15kHz, at 12dB SINAD)	-		0.5μV (28-29.9MHz)
	-		0.32μV
Squelch sensitivity	SSB, CW, RTTY, PSK: Less than 5.6μV (Pre-amp: OFF)		
	FM: Less than 1μV (Pre-amp: OFF)		
Selectivity	More than		Less than
	SSB (BW=2.4kHz, sharp)	2.4kHz/-3dB	3.6kHz/-60dB
CW/RTTY/PSK (BW=500Hz, sharp)	500Hz/-3dB		700Hz/-60dB
	AM (BW=6kHz)	6.0kHz/-3dB	15.0kHz/-60dB
FM (BW=15kHz)	12.0kHz/-6dB	20.0kHz/-60dB	
Spurious and image rejection ratio	More than 70dB		
Audio output power	More than 2.6W (10% distortion, 8Ω load)		
RIT variable range	±9.999kHz		
ANTENNA TUNER			
Matching impedance range	HF bands: 16.7Ω to 150Ω unbalanced (VSWR better than 3:1)		
	50MHz: 20Ω to 125Ω unbalanced (VSWR better than 2.5:1)		
Minimum operating power	HF bands: 8W		
	50MHz band: 15W		
Tuning accuracy	VSWR 1.5:1 or less		
Insertion loss	Less than 1.0 dB (after tuning)		

Supplied accessories: (* May differs depending on version)

- Rack mount handles
- SD card
- AC power cable
- Spare fuses
- Plugs

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.



IC-PW1/IC-PW1EURO

HF+50MHz 1kW LINEAR AMPLIFIER
Automatic antenna tuner and compact detachable controller are standard. 2 exciter inputs and 4 antenna connectors are available.

SP-34 EXTERNAL SPEAKER

4 audio filters; headphone jack; can connect to 2 transceivers.
Input impedance: 8Ω Max. input: 5W

SM-50 DESKTOP MICROPHONE

Dynamic microphone with [UP/DOWN] switches.

HM-36 HAND MICROPHONE



SP-33 EXTERNAL SPEAKER



SM-30 DESKTOP MICROPHONE



CT-17 CI-V LEVEL CONVERTER



RS-BA1 IP REMOTE CONTROL SOFTWARE



RC-28 USB REMOTE ENCODER



Icom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand, and/or other countries. Windows is either registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. All other trademarks are the properties of their respective holders.

Icom Inc.

1-1-32, Kami-minami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom America Inc.

12421 Willows Road NE,
Kirkland, WA 98034, U.S.A.
Phone: +1 (425) 454-8155
Fax: +1 (425) 454-1509
E-mail: sales@icomamerica.com
URL: <http://www.icomamerica.com>

Icom (Europe) GmbH

Communication Equipment
Auf der Krautweide 24
65812 Bad Soden am Taunus, Germany
Phone: +49 (6196) 76685-0
Fax: +49 (6196) 76685-50
E-mail: info@icomeurope.com
URL: <http://www.icomeurope.com>

Icom France s.a.s.

Zac de la Plaine,
1 Rue Brindejonc des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone: +33 (5) 61 36 03 03
Fax: +33 (5) 61 36 03 00
E-mail: icom@icom-france.com
URL: <http://www.icom-france.com>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone: +886 (02) 2559 1899
Fax: +886 (02) 2559 1874
E-mail: sales@asia-icom.com
URL: <http://www.asia-icom.com>

Your local distributor/dealer:

Icom Canada

Glenwood Centre #150-6165
Highway 17A, Delta, B.C.,
V4K 5B8, Canada
Phone: +1 (604) 952-4266
Fax: +1 (604) 952-0090
E-mail: info@icomcanada.com
URL: <http://www.icomcanada.com>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone: +34 (93) 590 26 70
Fax: +34 (93) 589 04 46
E-mail: icom@icomspain.com
URL: <http://www.icomspain.com>

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone: +61 (03) 9549 7500
Fax: +61 (03) 9549 7505
E-mail: sales@icom.net.au
URL: <http://www.icom.net.au>

Shanghai Icom Ltd.

No.101, Building 9, Caifuxingyuan Park,
No.188 Maoting Road, Chedun Town,
Songjiang District, Shanghai, 201611, China
Phone: +86 (021) 6153 2768
Fax: +86 (021) 5765 9987
E-mail: bjicom@bjicom.com
URL: <http://www.bjicom.com>

Icom Brazil

Rua Itororó, 444 Padre Eustáquio
Belo Horizonte MG,
CEP: 30720-450, Brazil
Phone: +55 (31) 3582 8847
Fax: +55 (31) 3582 8987
E-mail: sales@icombrasil.com

Icom (UK) Ltd.

Blacksale House, Altria Park,
Herne Bay, Kent, CT6 6GZ, U.K.
Phone: +44 (0) 1227 741741
Fax: +44 (0) 1227 741742
E-mail: info@icomuk.co.uk
URL: <http://www.icomuk.co.uk>

Icom New Zealand

39C Rennie Drive, Airport Oaks,
Auckland, New Zealand
Phone: +64 (09) 274 4062
Fax: +64 (09) 274 4708
E-mail: inquiries@icom.co.nz
URL: <http://www.icom.co.nz>

ICOM

THE TRANSCEIVER

IC-7851

唯一、無比

HF Excellence Unparalleled
Hear What You Couldn't Hear
See What You Couldn't See

